



• **XP-D300H** احساس دلپذیر از طراحی و رنگ ، سرعت بالا و درگاههای اتصال متنوع این پرینتر را نسبت به سایر دستگاهها متمایز می کند .

XP-D300H

پرینتر صدور فیش حرارتی

Highlights

- خروجی فیش از جلوی دستگاه
- درگاه های اتصال USB+SERIAL+LAN
- سرعت پرینت 300 mm/S
- ساپورت 2048KB بافر ورودی



Support network printing



Support GB18030



High speed printing



Avoid order missing



Support OPOS driver

Key features

Simple and fashion design

partial/full option cutter

easy paper loading structure design



Specifications

Printin method	Direct thermal
Printing speed	300mm/s
Paper width	79.5±0.5mm
Roll paper	80mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line 512 dots/line (80mm)
Line space	3.75mm (changeable using commands)
Character size	ANK. Font A: 12*24 dots Font B: 9*17 dots simplified/traditional Chinese: 24*24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JANB (EANB) /CODABAR/ITF/CODE39/C·DE93/CODE128
Code page	PC347 (Standard Europe, Katakana, PC860 Multilingual, PC860 Portuguese, PC863 Canadian-French, PC865 Nordic, West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 Cyrillic#2, PC852 Latin2, PC858, Iranll, Latvian, Arabic, PT151 1251
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC24V=2.5A
Cash drawer control	DC24V=1A
Interface	USB+Serial+Lan
Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0-45°C), humidity(10-80%)
Storage environment	Temperature (-10-60°C), humidity(10-90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.84 kg
Dimension	185x140x134mm (DxWxH)



خیابان قائم مقام فراهانی، خیابان گلریز، نبش کوچه شبینم، پلاک ۶، طبقه اول

تلفن : ۰۲۱ - ۴۳۴۹۷