



• **XP-470B** ایده آل برای آزمایشگاهها ، مراکز درمانی و داروخانه ها.

XP-470B

لیبل پریتر

Highlights

- سرعت چاپ : 127mm/s
- عرض چاپ : 108 میلیمتر
- درگاهای اتصال : usb+ micro sd
- وضوح چاپ : 203dpi



Key features

USB2.0 Interface, High Speed printer



Streamlined Industrial Design



Easy operation, maintenance



Resolution	8 dots/mm(203 DPI)
Printing method	Direct Thermal
Max .print speed	127 mm (4")/S
Max .print width	108 mm (4.25")
Max .print length	2286 mm (90")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	20-112mm (0.78"-4.4")
Media thickness	0.06 ~ 0.16 mm (2.36 ~ 6.3 mil)
Label length	10 ~ 2,286 mm (0.4" ~ 90")
Label roll capacity	127 mm (5") OD (outside wound)
Enclosure	Double-walled plastic
Physical dimension	240 mm (W) x 211 mm (H) x 166 mm (D)
Weight	2.15kg
Processor	32-bit RISC CPU
Memory	4MB Flash Memory 8MB SDRAM SD card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz Output: DC 24V, 2.5A, 60W
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: red, purple & blue)
Sensors	Black mark reflective sensor (position adjustable) Head open sensor Transmissive gap sensor
Internal fonts	8 alpha-numeric bitmap fonts Windows fonts are downloadable from software.
Barcode	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code: PDF-417, Maxicode, DataMatrix, QR code
Font and barcode rotation	0°, 90°, 180°, 270°
Printer language	TSPL(EPL, ZPL, DPL)
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC, CE, CCC, CB
Environmental concern	RoHS
Accessories	① Windows labeling software, driver and user manual CD ② quick start guide ③ USB cable ④ power cord ⑤ external switching power adapter ⑥ label spindle, fixing tab x 2
Factory options	① Real time clock ② Peel-off module
User options	① external roll mount (1" core) ② external roll mount board



خیابان قائم مقام فراهانی، خیابان گلریز، نبش کوچه شبینم، پلاک ۶، طبقه اول

تلفن : ۰۲۱ - ۴۳۴۹۷