



LP- 423 A

LP- 423 N

لیبل پرینتر

- ۱۲ ساعت کار پیوسته
- دقت کالیبره کردن بالا بدون اتلاف کاغذ
- بسیار زیبا و کاربردی
- دارای نرم افزار طراحی اختصاصی
- دارای حافظه داخلی و نمایشگر
- تعویض آسان رول لیبل و ریبون
- ارتباط مستقیم با ترازو، بارکدخوان و کیبرد بدون نیاز به کامپیوتر
- ساخت کشور تایوان



یکسال گارانتی مرکز خدمات

www.saamtadbir.com



هایپرمارکت



فروشگاهها

LP-423N _ LP-423A

لیبل پرنتر



MODEL	LP423N	LP433N	LP423A	LP433A
Printing method	Thermal Transfer /Thermal Direct			
Resolution	203 DPI	300 DPI	203 DPI	300 DPI
Max. print speed	127mm (5")/ Sec	102mm (4")/ Sec	127mm (5")/ Sec	102mm (4")/ Sec
Max. print width	101.6mm	101.6mm	101.6mm	101.6mm
Max. print length	4572 mm (180")	2032 mm (80")	4572 mm (180")	2032 mm (80")
Enclosure	Double-walled plastic			
Physical dimension	220mm(W) x 198mm(H) x 288mm(D) 8.7"(W) x 7.8"(H) x 11.3"(D)			
Weight	2.5 kg			
Label roll capacity	127 mm (5") OD			
Ribbon spec	300 m, Max. OD 67 mm, 1" core			
Ribbon width	100 m, Max. OD 38.25 mm, 0.5" core			
Ribbon width	25.4 mm ~ 110 mm (1" ~ 4.3")			
Processor	32-bit RISC CPU			
Memory	8MB Flash-ROM, 16MB SDRAM		8MB Flash-ROM, 16MB SDRAM, SD card slot for expansion up to 32GB	
Power	External universal power supply , Input: AC 100-240V, 2.5A, 50-60Hz, Output: DC 24V, 2.5A,			
OPreation switch BUtton. LED	1 feed button, 8 LEDs		4 buttons, 2 LEDs, 1 LCD (2.13", Resolution: 128x64), 1 Buzzer	
Interface	USB 2.0, RS-232		USB 2.0, RS-232, USB Host, Paral	
	Ethernet 10/100 Mbps (option), Bluetooth(option), Wireless 802.11 b/g/n (option)			
Sensors	Transmissive gap sensor, Reflective sensor (adjustable), Ribbon end sensor, Cover open sensor, Paper near-end sensor (option)			
Internal fonts	Seven kinds of bitmap fonts			
Bar code	1D bar code.Code 11, Code 39, Code 93, Code 128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2-of-5, ITF-14, MSI Pleassy, PostCode, Telepen, UPC-A, UPC-E, UCC-128, GS1-128, Standard 2 of 5, Industrial 2 of 5			
	2D bar code.Code 16K, Code 49, Aztec Code, QR Code, PDF417, Micro PDF417, Data Matrix, Grid Matrix, Micro QR Code, MaxiCode			
	GS1 Barcode.GTIN-13, GLN, GTIN-8, GTIN-14(ITF-14), SSCC, GS1-128, GS1 DataBar, GS1 Composite			
Printer language	WPL (Compatible to the other printer languages as ZPL, EPL, TSPL...etc)			
Dealer option	Cutter.Peeler dispenser.External label stand			
Media width	15 ~ 110 mm (0.59" ~ 4.3")			
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)			
Media core diameter	25.4 mm (1")			
Label length	3 ~ 4,572 mm (0.12" ~ 180")			
Real time clock	RTC (battery is not included)		RTC (battery is included)	
Storage condition	-40 ~ 60°C, 10~ 90% (non-condensing)			
Operation condition	5 ~ 40°C, 25 ~ 85% (non-condensing)			
Safety regulation	CE Class B, FCC Class B, CCC, CB, BIS			
Bundled software	"WinLabel" label design software, Windows printer driver, Printer utility, DLL SDK library, EXE executive AP for batch print. Platform support : Windows XP SP3, Vista, 7, 8, 8.1, 10 and Server 2003, 2008, 2012, 2012R2 (32/64 bi)			



خیابان قائم مقام فراهانی،
خیابان گلریز، پلاک ۶ طبقه اول

۰۲۱-۴۳۴۹۷

info@saamtadbir.com

www.saamtadbir.com

SAAM
TADBIR

شرکت صنایع سام تدبیر