



• **XP-C260H** نسل جدید پرینترهای صدور فیش همراه با پورت اتصال wifi را به مصرف کننده معرفی می نماید .

XP-C260H

پرینتر صدور فیش حرارتی

Highlights

- طراحی مناسب و کاربردی
- درگاههای اتصال USB+ Wifi
- دارای پوشش محافظ آب
- سرعت پرینت 260 mm/s



Support network printing



Support GB18030



High speed printing



Avoid order missing



Support OPOS driver

Key features


Simple and fashion design

partial/full option cutter

easy paper loading structure design



Specifications	
Printing method	Direct thermal
Printing speed	260mm/s
Paper width	80 mm
Paper diameter	80mm
Paper thickness	0.06-0.05mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75 mm (changeable using commands)
Character size	ANK, Font A: 24.12 dots Font B: 9*17 dots simplified/traditional Chinese: 24*24 dots
Bar code	UPC-NUPC-E/JAN13 (EAN13) /JANS /EANS /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE/PDF417
Code page	PC 347 (Standard Europe,) Katakana, PC 850 Multilingual , PC 860 Portuguese , PC 863 Canadian-French, PC 865 Nordic, West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC 866 (Cyrillic#2,) PC 852 (Latin2,) PC 858, Iran L Latvian, Arabic, PT151 (1251
NV FLASH	256 K Bytes
Input buffer	2048 K Bytes
Power supply	DC 24 V=2.5A
Cash drawer control	DC 24 V= 1A
Interface	Serial+USB+Lan/Wifi+USB/Bluetooth+USB
Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0-45°C), humidity(10-80%)
Storage environment	Temperature (-10-60°C), humidity(10-90%)
Drivers	Win9X/Win ME/Win2000 /Win 2003/Win NT/Win XP/Win Vista/Win7/Win8/Win10/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.81 kg
Dimension	193.3 x 145x144 mm (DxWxH)



خیابان قائم مقام فراهانی، خیابان گلریز، نبش کوچه شبینم، پلاک ۶، طبقه اول

تلفن : ۰۲۱ - ۴۳۴۹۷