

Xprinter



• **XP-T260M** با طراحی مدرن ، قطعات با کیفیت ژاپنی و در گاههای اتصال کامل بهترین انتخاب برای هر مصرف کننده می باشد .

XP-T260M

پرینتر صدور فیش حرارتی

Highlights

- خروجی فیش از جلوی دستگاه
- درگاههای اتصال USB+SERIAL+LAN
- هد قدرتمند ژاپنی
- سرعت پرینت ۳۰۰ mm/s
- ساپورت انواع سیستم عاملها



Support network printing



Support GB18030



High speed printing



Avoid order missing



Support OPOS driver

۱ سال گارانتی سام تدبیر
www.saamtadbir.com

Key features

Simple and fashion design

partial/full option cutter

easy paper loading structure design



Specifications:

Printing method	Direct thermal
Printing speed	300mm/s
Paper width	80mm
Paper diameter Paper thickness	80mm 0.06-0.08 mm
Column capacity Line space	576 dots/line 512 dots/line 3.75mm (changeable using commands)
Character size	ANK, Font A: 12*24 dots Font B: 9*17 dots simplified/traditional Chinese: 24*24 dots
Barcode	UPC-NUPC-E/JAN 13 (EAN13) /JANS (EANS) /C·DABAR/1TF/C·DE39/CODE93/C·DE128 QR CODE
Code page	PC 347 (Standard Europe, Katakana, PC850 Multilingual, PC860 Portuguese, PC 863 Canadian-French, PC865 Nordic, West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 Cyrillic#2, PC852 Latin2, PC858, IranII, Latvian, Arabic, PT151 1251
NV FLASH Input buffer Power supply Cash drawer control	256K Bytes 2048 K Bytes DC24V=2.5A DC24V=1A
Interface	Serial+USB+Lan
Auto cutter Reliability	Partial Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment Storage environment	Temperature (0-45°C), humidity(10-80%) Temperature (-10-60°C), humidity(10-90%)
Drivers Command Gross weight Dimension	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win7 /Win 8 /Win 10 /Linux/OPOS Compatible with ESC/POS 1.48 kg 185x140 x134mm (D xWx HJ)



خیابان قائم مقام فراهانی، خیابان گلریز، نبش کوچه شبینم، پلاک ۶، طبقه اول

تلفن : ۰۲۱ - ۴۳۴۹۷